

# The Synchrotron Light Facility in Brazil

Liu Lin  
LNLS Accelerator Physics Group

# LNLS – the Brazilian Synchrotron Light Laboratory



## About Brazil

Area	$8.5 \times 10^6 \text{ km}^2$	World rank 5 <sup>th</sup>
Population	202 million	World rank 5 <sup>th</sup>
GDP (2014)	\$2.35 trillion	World rank 7 <sup>th</sup>

Source: wolframalpha

- UVX – the only synchrotron in Latin America
- Over 85% built in Brazil
- Operating for users since July 1997.



# LNLS – the Brazilian Synchrotron Light Laboratory




## LNLS - CNPEM

- City of Campinas – State of São Paulo
- 100 km west from city of São Paulo
- Population: 1 million
- Close to Unicamp – University of Campinas, a public State university with 41 thousand students.

# The institution - CNPEM



“Organização Social”  
Private, non-profit organization  
that signs a Contract with MCTI



# The first machine - UVX



- ▶ Design and construction: 1987 to 1997
- ▶ Designed and built in Brazil
- ▶ The only synchrotron light source in Latin America

# LNLS: from scratch to a state-of-the-art machine in 30 years - Brief history



20<sup>a</sup> RAU  
REUNIÃO ANUAL DE  
USUÁRIOS DO LNLS

22 e 23 de fevereiro

Aldo Felix Craievich

First discussions: ~ 1981

Projeto Radiação Síncrotron  
CBPF/CNPq



*Centro Brasileiro de Pesquisas Físicas*

CBPF/CNPq  
Centro Brasileiro de  
Pesquisas Físicas

# Pre-history of LNLS



- September/1982 – **CNPq installs the PRS** (Projeto Radiação Síncrotron) to “perform a viability study for the creation of a Synchrotron National Lab.”
- **1982/1983** – meetings organized by CBPF, funded by CNPq



PROJETO  
RADIAÇÃO  
SINCROTRON

RIO DE JANEIRO

1983



CONSELHO NACIONAL DE DESENVOLVIMENTO CIENTÍFICO E TECNOLÓGICO - CNPq



CENTRO BRASILEIRO DE PESQUISAS FÍSICAS - CBPF

CBPF/PRS 007/83

COURS SUR LE RAYONNEMENT SYNCHROTRON

Y. PETROFF  
(L.U.R.E.)

CENTRO BRASILEIRO DE PESQUISAS FÍSICAS - CBPF

CBPF/PRS - 010/84

THE PHYSICS OF ELECTRON STORAGE RINGS.  
AN INTRODUCTION

M. SANDS  
UNIVERSITY OF CALIFORNIA

Publicação Especial do Centro Brasileiro de Pesquisas Físicas (CBPF)  
Série: Projeto de Radiação de Sincrotron (PRS), coordenado por  
Ramiro de Porto Alegre Muniz, Aldo F. Craievich

CBPF/PRS - 001/83 - Proposta preliminar do estudo de viabilidade para a implantação de um Laboratório Nacional de Radiação de Sincrotron

CBPF/PRS - 002/83 - Notícia sobre a proposta preliminar do estudo de viabilidade para a implantação de um Laboratório Nacional de Radiação de Sincrotron

CBPF/PRS - 003/83 - Encontro das Sociedades Científicas sobre a proposta preliminar do estudo de viabilidade para a implantação de um Laboratório Nacional de Radiação de Sincrotron

CBPF/PRS - 004/83 - Resumos dos trabalhos apresentados no Encontro sobre Técnicas e Aplicações da Radiação Sincrotron

CBPF/PRS - 005/83 - Round Table on Technical Aspects of Synchrotron Radiation

CBPF/PRS - 006/83 - Conceptual Design of a 1.2 GeV Storage Ring extending in the Hard X-Ray Region

CBPF/PRS - 007/83 - Cours sur le Rayonnement Synchrotron

CBPF/PRS - 008/83 - Anais do Encontro "Técnicas e Aplicações da Radiação Sincrotron"

CENTRO BRASILEIRO DE PESQUISAS FÍSICAS - CBPF

Diretor

Prof. Ramiro de Porto Alegre Muniz

Coordenador do Projeto Radiação Sincrotron

Prof. Roberto Lobo

# Pre-history of LNLS



- September/1982 – **CNPq install the PRS** (Projeto Radiação Síncrotron) to “perform a viability study for the creation of a Synchrotron National Lab.”
- 1982/1983 – meetings organized by CBPF, funded by CNPq
- 3/december/1984 – CNPq creates the LNRS – Laboratório Nacional de Radiação Síncrotron
- December 1984 – Campinas, São Carlos, Niterói and Rio de Janeiro present proposals to host the Lab
- **January/1985 – Small team (5 people) goes to Stanford (Projetc 1)**

# Pre-history of LNLS

- September/1982 – **CNPq install the PRS** (Projeto Radiação Síncrotron) to “perform a viability study for the creation of a Synchrotron National Lab.”
- 1982/1983 – meetings organized by CBPF, funded by CNPq
- 3/december/1984 – CNPq creates the LNRS – Laboratório Nacional de Radiação Síncrotron
- December 1984 – Campinas, São Carlos, Niterói and Rio de Janeiro present proposals to host the Lab
- **January/1985 – Small team (5 people) goes to Stanford (Projetc 1)**



# THE BRAZILIAN SYNCHROTRON RADIATION PROJECT

A.R.D.Rodrigues and R.Lobo  
P.O.Box 369  
13560 - São Carlos - SP - Brazil

The proposal for a brazilian national laboratory for synchrotron radiation is presented. The first design study led to a system consisting of a LINAC, an injection ring and a low emittance storage ring. The main ring is designed to be upgraded to 3GeV with an emittance of  $4 \cdot 10^{-8}$  rad.m. The design study also indicated the possibility of using the injection ring as a soft x-Rays/VUV source.



The case for a future national synchrotron radiation laboratory in Brazil was firstly discussed in 1981 by a group of physicists. The subject was further discussed by the community of condensed matter physicists in april 1982 and in a meeting of scientific societies in august 1982, wich recommended deeper studies. The case study with the support of the Brazilian Research Council (CNPq) started in september 1982 and its results were presentend in january 1984 in a second meeting of the scientic societies. The existence of such national laboratory was considered as a very efficient investiment in science and it was decided to continue with studies towards machine parameters definition and technical aspects involved in the constructions of the equipment. Here we present a first design, wich satisfies the performance established by these studies, for the National Laboratory for Synchrotron Radiation (LNRS).

## Construction and Commissioning of Dedicated Synchrotron Radiation Facilities

Proceedings of Workshop  
October 16-18, 1985

# Pre-history of LNLS



- September/1982 – **CNPq install the PRS** (Projeto Radiação Síncrotron) to “perform a viability study for the creation of a Synchrotron National Lab.”
- 1982/1983 – meetings organized by CBPF, funded by CNPq
- 3/december/1984 – CNPq creates the LNRS – Laboratório Nacional de Radiação Síncrotron
- December 1984 – Campinas, São Carlos, Niterói and Rio de Janeiro present proposals to host the Lab
- January/1985 – Small team (5 people) goes to Stanford (Projetc 1)
- **January/1985 – Campinas is chosen as the place**
- November/1985 – Minister Renato Archer announces the decision to build LNRS
- December/1986 – CNPq buys a building to host the first technical groups
- **June/1987 – the first team of LNRS (26 people) start to work in this building**

# Pre-history of LNLS



- September/1982 – CNPq install the PRS (Projeto Radiação Síncrotron) to “perform a viability study for the creation of a Synchrotron National Lab.”
- 1982/1983 – meetings organized by CBPF, funded by CNPq
- 3/december/1984 – CNPq creates the LNRS – Laboratório Nacional de Radiação Síncrotron
- December 1984 – Campinas, São Carlos, Niterói and Rio de Janeiro present proposals to host the Lab

**Even though the Project was moving forward, there were strong criticisms from the scientific community:**

- **Too much money on a single project**
- **Lack of technical knowledge/personnel**
- **Lack of users**

# First LNLS building

Development of all prototypes, installation of a 50 MeV LINAC and first beamlines




**Building**



Lack of personnel with knowledge in accelerator engineering and scientific instrumentation

The solution was to hire young people, most seeking for their first job, and train them in a “hands on” approach



Roberto Medeiros

**26/July/1991**

**Some of the young people that built LNLS – 2<sup>nd</sup> meeting of the International Advisory Committee**

# Training also the users



- In the early 80's, there were around 10 people in Brazil who new/used synchrotron radiation
- LNLS has been doing a continuous effort, since the very beginning, to form and train users through schools, workshops, sending people abroad, etc.

# Encontro

Técnicas e Aplicações da Radiação Síncrotron  
PRS/CBPF, Rio de Janeiro, agosto de 1983





220 participantes

- R. Lobo (CBPF)
- A. Craievich (CBPF)
- A. Moreira (CBPF)
- R. P. A. Muniz (CBPF)
- C. Tsallis (CBPF)
- A. Ribeiro Costa (CBPF)
- G. Bemsky (CBPF)
- J. Benuzzi (CBPF)
- J. Rogers (UNICAMP)
- R. A. Douglas (UNICAMP)
- S. Caticha-Ellis (UNICAMP)
- C.E.T. Gonçalves da Silva (UNICAMP)
- V. Baranauskas (UNICAMP)
- C. Suzuki (UNICAMP)
- Y. Mascarenhas (IFSC)
- A.R.D. Rodrigues (IFSC)
- A.J. Castro (IFSC)
- J. Slaets (IFSC)
- M. Aegeirter (IFSC)
- E.E. Castellano (IFSC)
- G. Moscati (IFUSP)
- R. Salinas (IFUSP)
- C. Pimentel (IFUSP)
- L.Q. do Amaral (IFUSP)
- B. Marechal (UFRJ)
- G.G. Bezerra de Souza (UFRJ)
- E. Zanotto (UFSCar)
- P. Viccaro (UFRGS)
- T. Polga (CTA)
- C. Cusatis (UFPr)
- W.G. Machado (UFGO)
- H. Wiedemann (Stanford University)
- J. Le Duff (LAL, Orsay)
- J. Doucet (Physique des Solides, Orsay)
- Y. Petroff (LURE, Orsay)

# I Workshop Synchrotron Light. Applications and Related Instrumentation

25-28 de julho de 1988



- A. Guinier, France
- R. Fourme, France
- J. Peisl, Germany
- G. Will, Germany
- G. Rossi, France
- K. Malek, France
- G. Schaffer, Germany

# I Workshop de Usuários

10-14 de dezembro de 1990



**1987**

...beginning with optimism and high inflation!



p. A14


Ciéncia e Tecnologia

**Laboratório de Síncrotron pode estar pronto em 1992**

Da Reportagem Local

O ministro da Ciência e Tecnologia, Renato Archer, deverá empossar no próximo dia 19 (quinta-feira), em cerimônia às 11h30 em Brasília, o primeiro conselheiro diretor do Laboratório Nacional de Luz Sincrotron, o mais importante projeto brasileiro em Física experimental da década de 80. O laboratório, vinculado ao Conselho Nacional de Desenvolvimento Científico e Tecnológico (CNPq), permanecerá vários anos sem verba para começar sua instalação — até setembro de 1986 só haviam sido liberados cerca de Cr\$ 500 mil, segundo seu diretor, o físico Cylene Gonçalves da Silva, 46, da Universidade

Industrial and non-industrial uses were the two main categories.



primeira página

# FOLHA DE S.PAULO

Gabinete de Radiodifusão: Ofício-Fran Filho - São Paulo, sábado, 10 de fevereiro de 1987 - Um jornal a serviço do Brasil - Ano 66 - P. 22-23-24 - RJ-22-23-24 - RJ-Rio de Janeiro, 1987

## *Inflação de 16,82% em janeiro é recorde e dispara o gatilho*

*Partículas viajam na velocidade da luz*

Irons são modernos aceleradores-particleus de forma circun-paralelos são empregados em grandes velocidades, te e manter os elétrons na trajetória adequada o Sincrotron aumenta seu campo magnético sincronizadamente (dá o seu nome).

No Sincrotron brasileiro as partículas que serão aceleradas são os elétrons. Eles são acelerados por anel final, de armazenagem, também ocorre a sincronização dos aumentos de velocidade e intensidade do campo magnético.

de juntas e, todavia, diretamente no qual as partículas a estas velocidades. Os modelos eram inviáveis, entretanto, entrando por uma porta e saindo pela outra. Para que os aceleradores legam paralelos circulares, onde se podem ter as velocidades desejadas, dando voltas, em um

A black and white photograph of a middle-aged man with dark hair, wearing glasses, a mustache, and a suit jacket over a white shirt and tie. He is looking slightly to his left.

Financeiras já cobram taxa recorde de 1.190%

*Caderneta rende 17,4% e recupera suas perdas*

As taxas de juros estabelecidas pelas financeiras no crédito direto ao consumidor atingiram esta semana o nível recorde de 12,00% a.a. (31,00% a.m.), segundo pesquisa realizada pela Associação das Empresas de Investimento, Crédito e Financiamento (Acrif). Embora permanecendo a 12,00% a.a. em suas empresas, as financeiras

do pagamento muito menor pelo beneficiário expandido no mercadinho, que é de 100% para pessoas de menor idade e para pessoas com mais de 65 anos de idade, aumentando a freguesia de famílias. O valor médio da pensão é de 104,80 reais, com uma variação entre o menor e o maior de 177,60 reais, e as alternativas foram identificadas por 1.000 beneficiários.

elerator Projects in Mexico – Guanajuato November 12, 2015.

# 1993-1995

## Magnets production

Luis Câmara



Nelson Chinaglia



Luis Câmara



Luis Câmara

## Design and Applications of a Toroidal Grating Beamline

A. Rubens B. de Castro<sup>1</sup> P. T. Fonseca<sup>1</sup> J. G. Pacheco  
J. E. Verdugo, M. S. Z. Graeff<sup>1</sup>, G. B. Fraguas<sup>1</sup>

*Laboratório Nacional de Luz Síncrotron/CNPq, Caixa Postal 6192, 13081-970, Campinas, SP, Brasil*

<sup>1</sup> also at *Instituto de Física "Gleb Wataghin", Universidade Estadual de Campinas Caixa Postal 6165, 13081-970, Campinas, SP*






Figure 1: The LNLS TGM beamline, as installed at CAMD (Baton Rouge-USA)

First beamline designed and built by LNLS is installed for testing at the Center for Advanced Microstructures and Devices (CAMD) at Louisiana State University (USA)



# 1990 a 1996 – Constructions at LNLS Campus



# May/1996 – assembly of ring concluded



6/11/1996



# Assembly of first beamlines



XAFS

TGM




Foto: Cesar Gómez

## Luz Síncrotron chega a Estação Experimental

A luz síncrotron chegou pela primeira vez a uma estação experimental acoplada ao anel de armazenamento do LNLS.

Foi às 22:10 horas do dia 28 de outubro de 1996 (segunda-feira).

A foto, obtida por Guilherme Tróglas, mostra a luz síncrotron chegando à clausura de amostra instalada na linha de luz TGM, controlada pelo Grupo de Instrumentação de Ultravioleta e Vácuo.

Procedendo este fato notável, no dia 25, sexta-feira, às 3:10 horas (madrugada), a equipe do Departamento de Projeto havia conseguido obter uma corrente armazenada de 11.9 mA (quase 12 milíampéres), a 1.15 GeV. Ou seja, 81% da corrente armazenada a 120 MeV sobreviveu quando elevada a 1.15 GeV.


**28 out 1996**

## Primeiro espectro da estrutura fina de absorção de raios X

Às 15 horas do domingo, dia 3 de novembro, foi obtido o primeiro espectro da absorção de Raios X na linha de luz D04B-XAFS do LNLS.


Pela primeira vez, foi medida a estrutura fina da absorção em torno da borda K do cobre, conforme gráfico abaixo.

Primerio espectro de absorção da borda K do cobre obtido no LNLS no dia 3 de novembro de 1996 às 15:00 hs



**03 nov 1996**

PRIMEIRO ESPECTRO DE SAXS OBTIDO NA LINHA DE LUZ DO LNLS  
 Amostra padrão de carbono vitrificado  
 (1-fev-97)



# April/1997 – open for users

## First call for proposals

### Beginning of operation as a National Lab with 5 beamlines



MCT-CNPQ  
LABORATÓRIO NACIONAL DE LUZ SÍNCRONTRON

BOLETIM  
LNLS 1997  
Nº 1  
ABRIL

N  
S  
sirius

## Laboratório começa a receber pesquisadores

CIENTISTAS JÁ PODEM ter acesso à fonte de luz síncrotron brasileira para realizar pesquisa científica. O Ministério da Ciência e Tecnologia e o Conselho Nacional de Desenvolvimento Científico e Tecnológico vão entregar o equipamento aos pesquisadores em maio.

O LNLS É UM CENTRO nacional de pesquisas, aberto a cientistas de qualquer nacionalidade que desenvolvem estudos de materiais, em níveis atômico e molecular, utilizando a luz síncrotron.

EM LINHAS DE LUZ E estações experimentais instaladas no LNLS, os pesquisadores encontram a

infra-estrutura adequada para realizar experimentos para aplicações em áreas da Física, Química, Ciência dos Materiais, Biologia e Ciências do Meio Ambiente.

CINCO LINHAS E ESTAÇÕES EXPERIMENTAIS estão em fase de testes e estarão abertas a usuários externos a partir de julho de 1997. Outras

*Visão parcial do anel de armazenamento de elétrons do LNLS com instrumentação que leva luz síncrotron até estações experimentais*



duas linhas estarão disponíveis a partir de setembro. Em fevereiro de 1998, a oitava linha de luz ficará pronta. As aplicações desta instrumentação científica estão descritas resumidamente neste Boletim.

AS PROPOSTAS SUBMETIDAS AO LNLS serão analisadas por referees. Três

aspectos são essenciais: relevância científica ou tecnológica do tema da pesquisa, competência dos cientistas autores da proposta e viabilidade técnica das experiências propostas com os equipamentos disponíveis no Laboratório.

O USUÁRIO ACADÉMICO não paga pelos fótons nem pela infra-estrutura básica disponível no LNLS. Em troca, assume o compromisso de publicar os resultados da pesquisa, tornando-os acessíveis para a comunidade científico-tecnológica.


NENHUM GRUPO DE pesquisa tem direito de uso exclusivo sobre equipamentos

instalados no LNLS. Esta diretriz institucional é aplicada aos equipamentos desenvolvidos e construídos por integrantes do quadro próprio do Laboratório ou por usuários externos.

O LNLS É UM INSTRUMENTO DE fomento à pesquisa que o CNPq coloca à disposição dos cientistas.


Formulário **Proposta de Pesquisa** está disponível na home-page do LNLS (<http://www.lnls.br>) ou pode ser solicitado à Secretaria de Apoio ao Usuário pelo e-mail "secre@lnls.br"

# The UVX user community





Year	Users From Mexico
2010	3
2011	5
2012	5
2013	1
2014	2

■ Other States ■ São Paulo ■ Other countries



# UVX Performance Parameters



2015: Jan - Jun


# UVX beamlines

## VUV and Soft X-ray (5)

- Toroidal Grating Monochromator (BM)
- Spherical Grating Monochromator (BM)
- Planar Grating Monochromator (undulator)
- Soft X-Rays Spectroscopy (BM)
- Infrared nanospectroscopy (BM)

## Hard X-ray (13)

- small angle X-ray scattering I (BM)
- small angle X-ray scattering II (BM)
- X-ray absorption spectroscopy (BM)
- dispersive X-ray absorption spectroscopy (BM)
- X-ray diffraction I (BM)
- X-ray diffraction II (BM)
- X-ray powder diffraction (BM)
- X-ray fluorescence (BM)
- X-ray imaging (BM)
- crystallography of macromolecules (BM)
- MAD protein crystallography (wiggler)
- X-ray absorption spectroscopy II (BM)
- Materials science (SC wiggler)




## VUV and Soft X-ray (5)

- Toroidal Grating Monochromator (BM)
- Spherical Grating Monochromator (BM)
- Planar Grating Monochromator (undulator)
- Soft X-Rays Spectroscopy (BM)
- Infrared nanospectroscopy (BM)

## Hard X-ray (13)

- small angle X-ray scatter
- small angle X-ray scatter
- X-ray absorption spectro
- dispersive X-ray absorpt
- X-ray diffraction I (BM)
- X-ray diffraction II (BM)
- X-ray powder diffraction
- X-ray fluorescence (BM)
- X-ray imaging (BM)
- crystallography of macromolecules (BM)
- MAD protein crystallography (wiggler)
- X-ray absorption spectroscopy II (BM)
- Materials science (SC wiggler)

Open for users since  
July 1997  
18 years of operation



An aerial photograph of the Sirius Synchrotron facility. The central feature is a large, circular, white building with a prominent entrance on top, surrounded by a track. To the left, there's a cluster of modern industrial buildings with white and blue facades. The entire complex is set against a backdrop of green fields and trees, with a road visible in the foreground.

# Sirius

**The new Brazilian  
Synchrotron Light Source**

# 2008 – Proposal to prepare a conceptual design of a new light source in presented to MCTI



**LNLS**  
Laboratório Nacional de Luz Síncrotron  
Conselho Natoinal de Desenvolvimento Científico e Tecnológico - CNPq - Ministério da Ciência e Tecnologia

**Ministério da Ciência e Tecnologia**  
**EPLAN**  
EMERGÊNCIA PARA O FUTURO GOVERNO FEDERAL

## LNLS-2: UMA NOVA FONTE DE LUZ SÍNCROTRON DE ALTO DESEMPENHO PARA O BRASIL

Proposta para Preparação de um Projeto Conceitual Detalhado

Laboratório Nacional de Luz Síncrotron  
**LNLS**



Campinas, Fevereiro de 2008

**2003 – In the 13<sup>th</sup> User Meeting, the users discussed the need to start studying the possibility of a new, more competitive, light source**

**2006 – Recommendation, in the 2006-2009 Strategic Plan of ABTLuS, that a task force should be created in LNLS to study a new, low emittance light source**



# 2009



## 1<sup>st</sup> Workshop LNLs-2: Scientific Cases 10 and 11 of February

## 2<sup>nd</sup> Workshop New Source: Scientific Case 27 and 28 of August



Many internal meetings to define the conceptual project



## SIRIUS (BR): A NEW BRAZILIAN SYNCHROTRON LIGHT SOURCE

L. Liu\*, X. R. Resende and A. R. D. Rodrigues

LNLS - Laboratório Nacional de Luz Síncrotron, CP 6192, 13084-971, Campinas, SP, Brazil.

### Abstract

We report on the status of Sirius, the new 3 GeV synchrotron light source currently being designed at the Brazilian Synchrotron Light Laboratory (LNLS) in Campinas, Brazil. The new light source will consist of a low emittance storage ring based on the use of permanent magnet technology for the dipoles. An innovative approach is adopted to enhance the performance of the storage ring dipoles by combining low field (0.5 T) magnets for the main beam deflection and a short slice of high field magnet. This short slice will create a high bending field (2.0 T) only over a short longitudinal extent, generating high critical photon energy with modest energy loss from the complete dipole. There are several attractive features in this proposal, including necessity for lower RF power, less heating of the vacuum chambers and possibility to reduce the beam emittance by placing the longitudinal field gradient at a favorable place.

### INTRODUCTION

In order to satisfy the future demand for synchrotron radiation in Brazil, a proposal for a new ring is being developed to replace the existing 1.37 GeV UVX light source, a facility that is being operated for users since July 1997 in Campinas, São Paulo. The proposed new source, Sirius, is a 3<sup>rd</sup> generation 3.0 GeV low emittance synchrotron light source facility to be built in the same LNLS site, as shown in Figure 1.

Many alternative lattices have been analysed in the last year, including the 2.5 GeV, 16 cell TBA lattice presented at PAC09 [1]. That design was based on the use of low field (0.45 T) permanent magnets for the storage ring dipoles. The use of permanent magnets can reduce both the investment and operation costs of the project with the elimination (or significant decrease) of power supplies and cooling systems. The low dipole field also favors emittance reduction by wigglers. There is however the considerable drawback of excluding hard x-ray bending magnet sources, which can have substantial demand from users since the beam size is naturally very small at dipole sources and some experiments do not need the high brightness of the insertion devices.

In the second half of 2009 a new idea came up that would allow the implementation of hard x-ray dipole radiation sources but would still preserve the benefits of low overall dipole radiation power. The idea is to combine the low bending field for the main beam deflection with a high magnetic field which extends over only a very short longitudinal length (a slice magnet, for 1° deflection) so that the hard x-ray radiation is produced only at the beamline exit. In addition, this high field slice could be

used to create a longitudinal bending field profile designed to help reducing the emittance. The idea was implemented in the new lattice design and, together with further considerations on the need to produce high brightness radiation up to about 100 keV, led to a modification of the project to a 3.0 GeV electron storage ring with 20 TBA cells. The permanent magnet dipoles now combine a low bending field of 0.5 T for the main beam deflection with a 2.0 T slice to produce hard x-ray bending magnet photons of 12 keV critical energy.




Figure 1: Aerial view of the LNLS site with the planned new Sirius light source.




### THE STORAGE RING LATTICE

#### *Linear optics – emittance optimization*

The 3.0 GeV low emittance Sirius lattice structure is of a modified TBA type, with the middle dipole split to accommodate the high field slice in its center, as shown in Figure 2. Concerning emittance reduction, the center of the middle dipole is the most favourable position to place the high field slice since this is where the so called H function is small [2]. In addition, this is also a proper position for the dipole synchrotron light port. Besides the longitudinal field variation, we also resort to other known recipes to reduce the emittance, specifically, the use of transverse field gradient in the dipoles to increase the horizontal damping partition number, the allowance of slightly positive values for the horizontal dispersion at the straight sections (thus breaking the achromatic condition), and the increase in the inner bending angle in the TBA cell with respect to the outer angles [3].

Based on the above guidelines along with the obvious (and conflicting) requirements of a low emittance lattice with large dynamic aperture and limited circumference, we propose a 20-cell modified TBA structure for Sirius. The total deflection per cell of 18° is divided into 5° for each outer dipole and 8° for the middle one. The latter, in

- Refinement of project
- Infra-structure
- First permanent magnet prototypes






- Initiative “Construção de uma Fonte de Luz Síncrotron de 3<sup>a</sup> geração” is incorporated in the Multiannual Plan 2012-2015 of the Federal Government
- Sirius Project is included in the National Strategic Plan for Science, Technology and Innovation ENCTI 2012-2015
- **Sirius Project is included in the 2012 Federal Budget Law**



# 2012

**Project mature enough to be presented to an International Committee – MAC (Machine Advisory Committee) – 18 to 20 of June**




# 2012 - Most important MAC recommendation

The present lattice design is excellent by today's standards, but the committee urges LNLS to **push for tomorrow's brightness standard (e.g. <1 nm emittance)**.

- Sirius presented to the Machine Advisory Committee meeting in June 2012:

Emittance: **1.7 nm.rad**

3-Bend Achromat, **480m** circumference




permanent magnets



- Sirius four months after 2012 MAC recommendation

Emittance: **0.28 nm.rad**

5-Bend Achromat, **518m** circumference



Electromagnetic magnets

7-m SS


6-m SS

# 2013 - Sirius @ CNPEM campus




- Schedule


- Nov. 2017 start of machine installations
- mid 2018 start of SR commissioning





# 2012-2014 – Executive project concluded



- Total area - 68.000 m<sup>2</sup>
- Special floor to minimize effects of vibration on the accelerator and beamlines




# Building



## Technical area

- Electrical energy
- Cooling water plant
- Compressed air
- Air conditioning
- LHe plant
- RF amplifiers
- Power supplies
- Control room

## Storage ring (3 GeV)



# 2014 – Landwork finished




October 2014

# 2014 – Construction started in December


- 40 months construction – conclusion in April 2018.
- Important milestone: September 2017 – tunnel ready to start assembling the accelerators.






# Sirius Accelerators Layout



Concentric storage ring and booster share the same tunnel



# 2015 – Present Status: LINAC




LINAC (150 MeV) – Order placed to SINAP (Shanghai Institute of Applied Physics)/China


# 2015 – Present Status: Booster




- All projects of magnets concluded and sent to WEG;
- Correctors already received;
- Prototypes of quads received;
- Order placed for the RF cavities (RI);
- Many prototypes fabricated: vacuum chamber, girders, RF amplifier, etc.






# Storage Ring Parameters



Beam energy	3.0	GeV
Circumference	518.4 m	m
Lattice	20 x 5BA	
Straight sections (SS)	10 x 7.5m; 10 x 6.5m	
# of SS for IDs	18	
Nominal current, top up	350	mA
Betatron tunes (H / V)	48.10 / 13.17	
<b>Hor. Emittance</b>	<b>240 – 150</b>	<b>pm.rad</b>
Vert. emittance ( $k=1\%$ )	2.4	pm.rad
Number of bunches	$864 = 2^5 \times 3^3$	
Natural bunch length	9 (2.6)	ps (mm)
Energy spread	0.095 – 0.086	%
RF frequency	500 MHz	MHz





# BC: Low Field + High Field Superbend



- Permanent magnet (NdFeB)
- Low field (0.6 T) with transverse gradient
- High field insert (3.2 T) superbend
  - 19 keV critical energy
  - 1.4° deflection
  - Hard X-rays produced only at beamline exit
  - Total energy loss/turn from dipoles = 532 keV

# Optical functions




- 10-fold symmetry, alternating high and low  $\beta_x$  straights. Achromatic.
- Other configurations under study, e.g. 5-fold symmetric, with fewer high  $\beta_x$  straights.

# Beam stay clear – required free aperture for the beam

Horizontal: limited by vacuum chamber at high  $\beta_x$  section. Corresponds to **full gap of 8 mm** in the horizontal plane for a 2 m long ID at the center of low  $\beta_x$  section.


Vertical: limited by a 2 meter long ID with **full gap of 4.5 mm** at the center of low  $\beta_x$  section.




# Non-linear dynamics

- Dynamic and momentum apertures optimized with 14 sextupole families. No octupoles.
- Optimization in progress including magnets measured data and different IDs. No EPUs with vertical polarization.
- 6D tracking with alignment and multipole errors, physical limitations (including IVUs at minimum gap), orbit, tune and coupling corrections.

## Dynamic aperture



## Momentum aperture



### Random gaussian errors

- Alignment, magnets:  $40\text{ }\mu\text{m}$
- Alignment, girders:  $80\text{ }\mu\text{m}$
- Roll:  $0.3\text{ mrad}$
- Excitation:  $0.05\text{ %}$
- Multipole:  $\Delta B/B_{x=12\text{ mm}} = 1 \times 10^{-4}$

### Orbit correction

- BPMs close to strong sextupoles and quadrupoles (BBA).
- BPMs: 180 (9/cell)
- CHs: 120 (slow) / 80 (fast)
- CVs: 120 (slow) / 80 (fast)

### Physical limitations

- straight sections:  $\varnothing = 24\text{ mm}$
- dipoles:  $\varnothing = 24\text{ mm}$
- IVUs: full gap =  $4.5\text{ mm}$ ,  $L=2\text{ m}$


# Operation Phases

	Phase 0 Commissioning	Phase 1 Initial User Mode	Phase 2 Final User Mode	
Maximum total current	100	100	350	mA
Current/bunch (uniform fill)	0.116	0.116	0.405	mA
Single bunch current	-	-	2	mA
RF Cavities	2 SC	2 SC	2 SC + 3HC	
Natural emittance*	0.24	0.19 <span style="color:red">21% ↓</span>	0.15 <span style="color:red">37% ↓</span>	nm.rad
IDs	-	6 IVUs, 2 EPUs	12 IVUs, 8 EPUs	
Natural energy spread*	0.095	0.091	0.086	%
Natural bunch length*	2.6	2.2	11.7	μm


\*Considering zero current

# Intra Beam Scattering effects

## Emmitance




## Energy spread




# Beam lifetime

	Comm. .	Ph. 1	Ph. 2	Ph. 2 500 mA	Ph. 2 SB	
Current	100	100	350	500	2	mA
Touschek	25.5	23.6	27.5	19.7	6.3	h
Elastic	69.1	35.2	35.2	35.2	35.2	h
Inelastic	49	49	49	49	49	h
<b>TOTAL</b>	<b>13.5</b>	<b>11.0</b>	<b>11.7</b>	<b>10.0</b>	<b>4.8</b>	<b>h</b>




# Slow orbit feedback and coupling correction




Random errors: Gaussian truncated at  $\pm 1\sigma$


	Dip	Quad	Sext	Girders	BPMs	
x, y	40	40	40	80	20	μm
Roll	0.3	0.3	0.3	0.3	-	mrad
Excit.	0.05	0.05	0.05	-	-	%




# Fast Orbit Feedback (FOFB)



## FOFB Model






## Special vacuum chamber





# Injection with Pulsed Multipole Magnet (PMM)

Injection process will be more transparent to users. Top-up requires injections every few minutes.





# Magnet girders/pedestals system

Taking  
advantage of  
mass  
attenuation  
and vibration  
damping of  
concrete  
pedestals



# Pedestal stiffness measurement

Pedestal position on top of DIAMOND slab




Measured stiffness (10-150Hz)

Direction	Stiffness [N/ $\mu\text{m}$ ]
X-direction	770
Y-direction	410
Z-direction, excluding floor	4900
Z-direction, including floor	2000

Low stiffness in X and Y directions

Slab stiffness is lower than girder's

# Girder free mode measurements







Accelerometers  
installed in 35  
positions

Isolation springs  
(2Hz resonance)


Girder  
based on  
PETRA III  
design

Lowest modes	Frequency [Hz]	Predicted by FEM [Hz]
Y-bending	319	322
Torsion	333	352
Z-bending	354	354
Plate membrane mode	501	
Second order Z-bending	552	




# Magnet/girders/pedestals vibration measurements


Girder  
based on  
PETRA III  
design



900N  
Shaker  
Shaker  
Force




# Slab to girder transmissibility measurements



Stiff supports (bolts tightened)


Stiff supports (bolts loosened)

With Nivel



# Integrated magnet/girder design



Magnets with low center of mass with respect to girder



## Work flow




1. Preliminary magnetic design
2. Full mechanical design taking into account vibration and alignment
3. Magnetic design refinement

Stiff magnet/ girder connection to increase vibrational resonances  
 → alignment by construction





# Latest girder design

Complete system modal analysis:



Complete system simulations with the UVX slab power spectrum as input:




# Full NEG coated storage ring copper vacuum chamber

## Pros (full NEG coated strategy):

- Simple chamber's design
- More compact -> space saving
- Low photon desorption -> fast vacuum conditioning


## Cons (full NEG coated strategy):

- Limited number of activations
- High temperature (200°C) bake-out for NEG activation
- Many bellows to accommodate chamber's expansion during bake-out




# Low RF-impedance vacuum flange development

Chain-clamp design




Copper



UHV leak tight with  
3.5 N.m (<5E-10mbar·ls)



Keyhole design





to be TIG welded to  
copper vacuum  
chamber

100's of flanges  
in the ring!



# Vacuum - NEG coating R&D for narrow gaps




## Coating procedure (2 steps):

1. Coating of the circular profile
2. Coating of the narrow gap – “keyhole” sector

Coating thickness set to 2µm

NEG film activation  
(XPS analysis)



Figure of merit: oxygen 1s peak area reduction [%]





# Multipole kicker

A pulsed multipole magnet will be used to improve stored beam shaking during topup








# Multipole kicker

Half-sine of Current	1.64μs
Voltage	1000A
Inductance	5612V
Resistance	8.1μH
Peak field @ x =	0.06Ω
Peak field @ x = 7.7mm	0.070Tesla
Field @ x = ±1 mm	7.7mm
	0.000
	3Tesla


PMM field map at 1000A, 152kHz and a 10μm Ti coating.



# Beam position monitors - button geometry choice

## Step-Shaped BPM Button


Based on the geometry style implemented at ALBA.



**Input power**

## Flat BPM Button


Reduced ceramics dimensions to decrease wakelosses.



**37% reduction**

## Bell-Shaped BPM Button


Conical profile shifts the HOMs to higher frequencies and hide the ceramics from the beam.







**50% reduction**

From electromagnetic (wakefield) simulations, wakelosses are calculated

# Beam position monitors - button design



# Beam position monitors - prototypes







# BPM Electronics and firmware

## Open Hardware development

Requirements for Sirius RF BPM electronics

Parameter	Target Spec	Obtained
Resolution ( $0.1 \text{ Hz} - 1 \text{ kHz}$ ) @ $500 \text{ mA}$	80 nm	$\sim 50 \text{ nm}$
Long term stability (RMS)	140 nm	$< 140 \text{ nm}$

RF Front-End (diagonal channels)



Commercial MicroTCA crate



FMC standard 130 MSP/s 16-bit ADC board




AMC FMC carrier  
Designed by Warsaw University of Technology (WUT) for LNLS







# BPM Electronics



RF front-ends

Tests performed at SPEAR3 (SLAC/SSRL)



Complete rack test @ LNLS



a)

# Solid State RF Amplifier (SSA) @ LNLS

Collaboration with LURE/SOLEIL  
since 1999


(special tanks to Ti Ruan)

1999 - Prototype module with 230W

2001 - Booster operating with 900W

2007 – Booster upgraded to 2.2kW


2010 – Storage Ring operating with  
2 x 50 kW SSA





- High reliability
- No beam loss due to module failures
- 4 years in routine operation – 7 modules failed (out of 324), 6 fixed in house
- Whole SSA – 4 beam losses in 4 years due to failures in water flow meters and power supplies



# RF systems



- **Booster Solid State Amplifier**
  - 4.5 kW prototype assembled and tested (33dB gain)
  - Long term reliability tests performed
  - 50 kW SSA designed
- **Storage Ring Amplifiers**
  - Studying a new design
- **RF cavities**
  - Booster cavity ordered (PETRA 5 cell)
  - SR SC cavities purchasing process started
    - Effective HOM damping
    - Lower broadband impedance
    - Smaller number of RF plants: 2 cavities in one straight section








# Development of digital PWM current supplies

18bit-resolution  
ADC

150ps resolution  
Digital PWM



# Thank you

